

Maintenance guide

In order to receive the full benefit of the warranty system, customers will need to adhere to the EXOLUX maintenance guidelines and requirements as outlined below.

ClickDeck® has been designed using mill finish aluminium which provides the structure with a natural resistance to corrosive conditions. The ClickDeck® system is designed to be durable with minimal care, however it is important that you maintain it in accordance with proper practices. Mill finish aluminium requires regular cleaning to preserve a good standard of appearance/condition. To ensure you receive the full benefit of your warranty, please maintain your deck in line with with Australian and New Zealand Standard 2312 (AS/NZS2312) and the associated requirements of the atmospheric conditions and the corrosivity of particular environmental factors as outlined below. In order to maintain the quality of the system, it will need to be thoroughly rinsed with fresh water and desalinator in line with the applicable corrosivity category as outlined below:

Australian and New Zealand Standard 2312 (AS/NZS2312)

Corrosivity Category	Corrosivity	Typical Outdoor environments	Care required
C1	Very Low	Alpine areas	Thoroughly rinse with fresh water and desalinator every 6 months.
C2	Low	Arid/rural/urban; at least 50km from coast or sources of pollution	Thoroughly rinse with fresh water and desalinator every 6 months.
C3	Medium	Coastal areas with low salinity	Thoroughly rinse with fresh water and desalinator every 6 months.
C4	High	Sea-shore (calm) up to 1km from coast	Thoroughly rinse with fresh water and desalinator every 3 months.
C5-I	Very high (Industrial)	Aggressive Industrial areas, where environment may be acidic	Thoroughly rinse with fresh water and desalinator every 3 months.
C5- M	Very High (Marine)	Offshore and beachfront (rough seas and surf beaches)	Thoroughly rinse with fresh water and desalinator every 3 months.
CX	Extreme	Shoreline (Severe Surf)	Thoroughly rinse with fresh water and desalinator every month.

When maintaining ClickDeck® system it is important to avoid the following:

- Strong acids, alkaline substances or other materials/products that they may cause corrosion.
- Strong solvents including; thinners, petrol, diesel, turps or kerosene.
- Degreasers, pesticides, brand name lubricants or agents of unknown composition
- Laundry or dish detergents, oven cleaners or other harmful chemicals
- Chemicals/products that are warmer than 25°C during cleaning
- Abrasive materials and tools
- Build-up of debris, agents or moisture, to reside for any extended period of time.
- Immersion in soil, water or concrete.

Disclaimer:

Please note, failure to adhere to and maintain the ClickDeck® system in accordance with the Australian and New Zealand Standard 2312 (AS/NZS2312) and the requirements as outlined in this maintenance guide will impact the consumers' ability to obtain the full benefits of the warranty system.

